



BELL FENCE
S U P P L Y

WWW.BELLFENCE.COM



BF40

**Domestic High Tensile Strength
Galvanized Pipe**

Be American, Buy American!

BF40

BE AMERICAN, BUY AMERICAN!

- Designed specifically for fence applications
- Very rigid and strong pipe with a high tensile bending strength of 50,000psi
- Made in the U.S.A (Meets "Buy America" Requirements)
- Outperforms SCH40 in both strength and corrosion resistance
- Meets and/or succeeds the following specifications:
 - RR F-191 Chain Link Fence Specification
 - M-181 AASHTO
 - ASTM A513
 - ASTM F-1043 Group IC, IC-L



BF 40 vs. Schedule 40

Posts		Outside Dimensions	Pipe Wall Thickness (in.)	Weight (lbs./ft)	Section Modulus (lbs./ft)	Yield Strength (inches ³)	Bending Moment (psi)	Bending Strength (lbs. in.) 6' Cantilever Load	Bundle Counts (lbs.)
1-7/8" O.D.	MT 40	1.900	.120	2.28	0.2810	50,000	14,050	195	61
	Sch 40	1.900	.145	2.72	0.3262	30,000	9,786	136	
2-3/8" O.D.	MT 40	2.375	.130	3.12	0.4881	50,000	24,405	339	37
	Sch 40	2.375	.154	3.65	0.5606	30,000	16,818	234	
2-7/8" O.D.	MT 40	2.875	.160	4.64	0.8778	50,000	43,890	610	30
	Sch 40	2.875	.203	5.79	1.0640	30,000	31,920	443	
3-1/2" O.D.	MT 40	3.500	.160	5.71	1.3408	50,000	67,040	931	19
	Sch 40	3.500	.216	7.58	1.7241	30,000	51,723	718	
4" O.D.	MT 40	4.000	.160	6.56	1.7819	50,000	89,095	1237	19
	Sch 40	4.000	.226	9.11	2.3940	30,000	71,820	998	
Top Rail								10' Supported	
1-5/8" O.D.	MT 40	1.660	.111	1.84	0.1961	50,000	9,805	327	61
	Sch 40	1.660	.140	2.27	0.2350	30,000	7,050	235	

QUALITY PRODUCTS

CUSTOMER SERVICE

COMPETITIVE PRICES

BEAUMONT, TX ■ BRYAN, TX ■ CORPUS CHRISTI, TX ■ LA FERIA, TX ■ LAFAYETTE, LA ■
BATON ROUGE, LA ■ JACKSON, MS ■ SHREVEPORT, LA ■ WEST MONROE, LA ■ MOBILE, AL ■
PENSACOLA, FL ■ ROBERTSDALE, AL

WWW.BELLFENCE.COM ■ PHONE (800) 877-2355 ■ FAX (409) 833-5014